

SEE Cable Terminal

Insulated Pin Terminals

Material
Insulation: PVC
Terminal Body: Copper
Plating: Tin



Wire range: 0.5~1.5mm² (A.W.G. 22~16)

I_{max}=19A

Item No	Dimension(mm)				Color
	F	L	H	D φ	
PTV1.25-9	1.9	19.0	10.0	4.3	Red
PTV1.25-10	1.9	20.0			
PTV1.25-12	1.9	22.0			
PTV1.25-13	1.9	23.0			
PTV1.25-18	1.9	28.0			

Wire range: 1.5~2.5mm² (A.W.G. 16~14)

I_{max}=27A

Item No	Dimension(mm)				Color
	F	L	H	D φ	
PTV2-9	1.9	19.0	10.0	4.9	Blue
PTV2-10	1.9	20.0			
PTV2-12	1.9	22.0			
PTV2-13	1.9	23.0			
PTV2-18	1.9	28.0			

Wire range: 2.5~4mm² (A.W.G. 14~12)


I_{max}=37A

Item No	Dimension(mm)				Color
	F	L	H	D φ	
PTV3.5-10	2.8	20.0	13.0	6.2	Black
PTV3.5-13	2.8	25.5			

Wire range: 4~6mm² (A.W.G. 12~10)

I_{max}=48A

Item No	Dimension(mm)				Color
	F	L	H	D φ	
PTV5.5-13	2.8	25.5	13.0	6.7	Yellow



Insulated Butt Connectors

Material
Insulation: PVC
Terminal Body: Copper
Plating: Tin

型号规格 Item No	尺寸Dimension(mm)			电线范围 Wire range		最大电流 I _{max}	颜色 Color
	l	d φ	L	A.W.G.	mm ²		
BV1.2 5	15.0	1.7	26.0	22-16	0.5-1.5	19A	红色 Red
BV2	15.0	2.3	26.0	16-14	1.5-2.5	27A	蓝色 Blue
BV5.5	15.0	3.4	26.0	12-10	4-6	48A	黄色 Yellow
BV8	21.0	4.5	32.0	8	6-10	62A	红色 Red
BV14	26.0	5.8	42.0	6	10-16	88A	蓝色 Blue
BV22	29.0	7.7	50.0	4	16-25	115A	黄色 Yellow
BV38	32.0	9.4	55.0	2	25-35	160A	红色 Red

