

SAFETY CANS

TYPE I SAFETY CANS

FLAMMABLES							
Model Numbers	UI-2-S	UI-4-S	UI-10-S	UI-20-S	UI-25-S*	UI-50-S	
Model-w/Funnel	–	–	UI-10-FS	UI-20-FS	UI-25-FS*	UI-50-FS	
Capacity	1qt.	2qt.	1gal.	2gal.	2½gal.	5gal.	
Dimensions WxH	5¼" W 8" H	9" W 5⅝" H	9" W 8" H	11¼" W 9½" H	11¼" W 10" H	12½" W 13½" H	
Weight	1.96 lbs.	2.25 lbs.	3.52 lbs.	5.25 lbs.	5.7 lbs.	7.00 lbs.	
Construction	Galvanized	Galvanized	Galvanized	Galvanized	Galvanized	Galvanized	Galvanized

TYPE I SAFETY CANS

DIESEL							
Model Numbers	UI-2-SY	UI-4-SY	UI-10-SY	UI-20-SY	UI-25-SY*	UI-50-SY	
Model-w/Funnel	–	–	UI-10-FSY	UI-20-FSY	UI-25-FSY*	UI-50-FSY	
Capacity	1qt.	2qt.	1gal.	2gal.	2½gal.	5gal.	
Dimensions WxH	5¼" W 8" H	9" W 5⅝" H	9" W 8" H	11¼" W 9½" H	11¼" W 10" H	12½" W 13½" H	
Weight	1.96 lbs.	2.25 lbs.	3.52 lbs.	5.25 lbs.	5.7 lbs.	7.00 lbs.	
Construction	Galvanized	Galvanized	Galvanized	Galvanized	Galvanized	Galvanized	Galvanized

TYPE I SAFETY CANS

- Eagle galvanized Type-I Safety Cans meet OSHA and NFPA Code 30 requirements and are UL and ULC listed and FM Approved for safe handling and storage of gasoline and other flammable liquids
- Eagle cans are constructed of 24-gauge hot dipped galvanized steel. Other manufacturers' safety cans use lead coated terne steel
- Accepted under CARB
- UL, ULC and FM Approved

- Also available in blue for the storage of kerosene, yellow for the storage of diesel and green for the storage of combustible liquids, such as oils








* Meets the New York City Fire Code Title 29 FC 2204.4.4.1.1 Maximum 2.5 gallon container regulations

Compliance: OSHA 29 CFR 1910.106, 1926.152 and NFPA Code 30










SAFETY CANS

TYPE I SAFETY CANS

KEROSENE							
							
Model Numbers	UI-2-SB	UI-4-SB	UI-10-SB	UI-20-SB	UI-25-SB	UI-50-SB	
Model-w/Funnel	—	—	UI-10-FSB	UI-20-FSB	UI-25-FSB	UI-50-FSB	
Capacity	1qt.	2qt.	1gal.	2gal.	2½gal.	5gal.	
Dimensions WxH	5¼" W 8" H	9" W 5½" H	9" W 8" H	11¼" W 9½" H	11¼" W 10" H	12½" W 13½" H	
Weight	1.96 lbs.	2.25 lbs.	3.52 lbs.	5.25 lbs.	5.7 lbs.	7.00 lbs.	
Construction	Galvanized	Galvanized	Galvanized	Galvanized	Galvanized	Galvanized	

TYPE I SAFETY CANS

COMBUSTIBLES							
							
Model Numbers	UI-2-SG	UI-4-SG	UI-10-SG	UI-20-SG	UI-25-SG	UI-50-SG	
Model-w/Funnel	—	—	UI-10-FSG	UI-20-FSG	UI-25-FSG	UI-50-FSG	
Capacity	1qt.	2qt.	1gal.	2gal.	2½gal.	5gal.	
Dimensions WxH	5¼" W 8" H	9" W 5½" H	9" W 8" H	11¼" W 9½" H	11¼" W 10" H	12½" W 13½" H	
Weight	1.96 lbs.	2.25 lbs.	3.52 lbs.	5.25 lbs.	5.7 lbs.	7 lbs.	
Construction	Galvanized	Galvanized	Galvanized	Galvanized	Galvanized	Galvanized	

Type I Safety Cans:

- Eagle galvanized Type-I Safety Cans meet OSHA and NFPA Code 30 requirements and are UL and ULC listed and FM Approved for safe handling and storage of gasoline and other flammable liquids
 - Eagle cans feature environmentally friendly lead-free technology, constructed of 24-gauge hot dipped galvanized steel (Other manufacturers' safety cans use lead coated terne steel)
 - UL, ULC and FM Approved
- Compliance: OSHA 29 CFR 1910.106, 1926.152 and NFPA Code 30



F-15 Funnel



SAFETY CANS

TYPE I POLY CANS

TYPE I STAINLESS

Model Numbers	1535	1541	1537	1543	1533	1539	1313	1315
Capacity	3gal.	5gal.	3gal.	5gal.	3gal.	5gal.	2 1/2gal.	5gal.
Dimensions WxH	12½" W 13" H	12½" W 17" H	12½" W 13" H	12½" W 17" H	12½" W 13" H	12½" W 17" H	11¼" W 9½" H	11¼" W 15½" H
Weight	6 lbs.	7 lbs.	6 lbs.	7 lbs.	6 lbs.	7 lbs.	8 lbs.	10 lbs.
Construction	Poly	Poly	Poly	Poly	Poly	Poly	Stainless Steel	Stainless Steel

TYPE II SAFETY CANS

	FLAMMABLES	KEROSENE		DIESEL		COMBUSTIBLES		
Model 7/8" Spout	U2-26-S	U2-51-S	U2-26-SB	U2-51-SB	U2-26-SY	U2-51-SY	U2-26-SG	U2-51-SG
Model 5/8" Spout	U2-26SX5	U2-51-SX5	U2-26SX5B	U2-51-SX5B	U2-26SX5Y	U2-51-SX5Y	U2-26SX5G	U2-51-SX5G
Capacity	2gal.	5gal.	2gal.	5gal.	2gal.	5gal.	2gal.	5gal.
Dimensions WxH	11¼" W 9½" H	11¼" W 15½" H	11¼" W 9½" H	11¼" W 15½" H	11¼" W 9½" H	11¼" W 15½" H	11¼" W 9½" H	11¼" W 15½" H
Weight	8 lbs.	10 lbs.	8 lbs.	10 lbs.	8 lbs.	10 lbs.	8 lbs.	10 lbs.
Construction	Galvanized	Galvanized	Galvanized	Galvanized	Galvanized	Galvanized	Galvanized	Galvanized

Type II Safety Cans:

- Eagle Type II Safety Cans are made of galvanized steel and help reduce the danger of explosion while dispensing flammable liquids through a flexible 12" metal spout
- Flame arrestors in filler opening and pour spout

Compliance: OSHA 29 CFR 1910.106, 1926.152 and NFPA Code 30

- Metal Safety Cans are FM, UL and ULC Approved and meet OSHA and NFPA Code 30 requirements. Poly Cans are FM Approved




















F-16 Funnel

(For use with Poly Type I Cans)









SAFETY CANS

LAB CANS

	STAINLESS	METAL	POLY					
								
Model Numbers	1301	1401	1512	1513	1510	1511	1508	1509
Approvals								
Capacity	1gal.	1gal.	1/2 gal.	1gal.	1/2 gal.	1gal.	1/2 gal.	1gal.
Dimensions WxDxH	6" W 8" D 13" H	6" W 8" D 13" H	6" W 8½" D 9½" H	6" W 8½" D 13" H	6" W 8½" D 9½" H	6" W 8½" D 13" H	6" W 8½" D 9½" H	6" W 8½" D 13" H
Weight	3.75 lbs.	3.75 lbs.	2.5 lbs.	2.8 lbs.	2.5 lbs.	2.8 lbs.	2.5 lbs.	2.8 lbs.
Construction	Stainless	Coated Metal	Poly	Poly	Poly	Poly	Poly	Poly

FAUCET CANS

DOT CANS

						
Model Numbers	1417	1327	1215	1215-SX5	1215Y	1215Y-SX5
Approvals			—	—	—	—
Capacity	5gal.	5gal.	5gal.	5gal.	5gal.	5gal.
Dimensions WxD	12½" W 13½" D	11¼" W 15¾" D	12½" W 15¾" D	12½" W 15¾" D	12½" W 15¾" D	12½" W 15¾" D
Weight	12 lbs.	9 lbs.	13 lbs.	13 lbs.	13 lbs.	13 lbs.
Construction	Galvanized	Stainless	Galvanized	Galvanized	Galvanized	Galvanized

Laboratory Safety Cans:

- Laboratory Safety Cans reduce the danger of explosions resulting from the ignition of vapors of flammable liquids
- Cans are available in coated metal, stainless steel and high-density polyethylene for safe storage and handling of most chemical compounds

Compliance: OSHA 29 CFR 1910.106,
1925.152 & NFPA Code 30

DOT Transport Type II Safety Cans:

- Reduce the danger of explosion while dispensing flammable liquids through a flexible metal spout
- Have double-walled flame arrestors in filler opening and pour spout
- Heavy duty roll bars protect both spouts, and a thumb screw mechanism assures the filler opening stays closed while being transported
- Meet DOT requirements

Compliance: OSHA 29 CFR 1910.106, 1925.152 & NFPA
Code 30 - UN/DOT-1A1/Y1.2/100/08/USA/M4990/0.6mm